

Multimedia Projector

Vivitek DW81DAA

Wide screen projection for the ultimate viewing pleasure



- 4,000 ANSI lumens of brightness with a 20,000 contrast ratio
- Energy efficient lamps that last up to 7,000 hours (in dynamic eco. mode)
- 6 Segment (RYGCWB) color wheel for accurate and detailed images
- Sealed optical engine, minimizing the impact of dust and smoke
- Quick auto search filtering to quickly locate input signal source
- Variety of display connectivity options including: HDMI, VGA-in (2x), VGA-Out, S-Video and Composite Video
- User memory settings for such functions as display mode, 3D and resolution
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-Ray support for dazzling and realistic life-like images
- Compatible with long VGA cables for a maximum length up to 20 meters
- Enhanced environmentally friendly power functions (Eco mode, Auto power off, stand-by mode) to increase lamp life, power savings and energy consumption
- Internal audio speaker delivers 10W of total audio power
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Top-loading, sliding cover for quick and easy lamp replacement
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad

Specifications

Display Type	Single 0.65" DLP Technology by TI
Brightness	4,000 ANSI Lumens
Native Resolution	WXGA (1280x800)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	20,000:1
Lamp Life/Type	3500/5000/7000 Hours (Normal/Eco.Mode/Dynamic Eco Mode), 240W/190W
Throw Ratio	1.28 - 1.536
Image Size (Diagonal)	30.2" - 302.3"
Projection Distance	1 - 10m (3.28ft to 32.8ft)
Projection Lens	F2.5 - 2.72 , f=17.81 - 21.35mm
Zoom Ratio	1.2x
Aspect Ratio	16:10 Native
Offset (Vertical)	111.3% (±5%)
Keystone Correction	±40 Degree; ±40 Steps
Horizontal Frequency	15, 31 - 91Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D Compatibility	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
Audio	10W (Mono)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4b, VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack)(x3), VGA-Out, USB (Type A for 5V/1.5A Power Only), Audio-Out (Mini-Jack), RJ45, RS-232, Mini-USB (Service), Microphone (Mini-Jack), 12V Trigger
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	314 x 216 x 126mm (12.4" x 8.5" x 4.9")
Weight	3.05kg (6.7lbs)
Available Color	Two-Tone: White/Gray
Noise Level	36dB/32dB (Normal/Eco. Mode)
Power Supply	AC 110-240V, 50/60Hz
Power Consumption	250W (Eco. Mode), 310W (Normal Mode), <0.5W (Standby Mode), <6W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	Replacement Lamp, RS-232 Cable, Filter (China only)

©2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



Photos

